

Amendments to the specification

Please amend the paragraph at page 8, line 15 of the application as follows.

The first interlocking member 5 includes two spaced apart first tabs ~~51~~—52 projecting outwardly from the second wall portion 302 of the recess-confining wall 30 in the transverse direction. Each of the first tabs 52 has top and bottom surfaces 522, 523. The top surface 522 of one of the first tabs 52 is formed with a retaining groove 521. The cover 3 has an upper surface 303. The second interlocking member 7 includes two spaced apart second tabs 72 projecting downwardly from the second side 302 of the cover 3 and then projecting laterally relative to the upper surface 303 of the cover 3 in a direction away from the second side 302 of the cover 3, and an intermediate tab 73 disposed between the second tabs 72 and projecting upwardly from the second side 302 of the cover 3 and then projecting laterally relative to the upper surface 303 of the cover 3 in the direction away from the second side 302 of the cover 3. The intermediate tab 73 is formed with a retaining boss 731. The first and second interlocking members 5, 7 are engageable (see Fig. 8) with each other in such a manner that the second tabs 72 are respectively disposed below and abut against the bottom sides 523 of the first tabs 52, that the intermediate tab 73 is disposed above said one of the first tabs 52 and abuts against the top surface 522 of said one of the first tabs 52, and that the retaining boss 731 engages the retaining groove 521.